

APPLICATIONS

A



Concave
Long leads, terminal
and Wire Wrap pads



B



Conic head 30°
Cuts oxidation and
contamination



F




Flat Head
Gold edge fingers,
leaves no marks



B12



HSS needle
Cuts oxidation
and contamination



D



Dome head
Gold edge fingers,
plated through holes
leaves no marks



BD



Conic with dome tip
Circuitry and Testpads,
leaves no marks




E




Conical
Plated through holes



BT75



Pyramid (75°)
Very aggressive,
general purpose steel
hardened nickel/gold
plated




T




3 sided chisel (45°)
Plated through holes,
cuts through
contamination



B9



HSS needle
For contaminated
and unwashed
PC boards




T4




6 fluted star
Plated through holes,
pads, lands



N



HSS flexible needle
For contaminated
and unwashed
PC boards



P



6 sided chisel
Plated through holes,
cuts through
contamination




ZT



Spear HSS
Very aggressive,
general purpose steel
hardened nickel/gold
plated




U




0,3 mm
0,4 mm
0,53 mm


3-point crown
Suitable for SMD testing
due to small head
diameter




Z




8-point crown
Similar application
like Tip L



HS



SMD serrated 4 points
Small pads and lands, no bridge risks (0,6 mm)



LS



SMD 4 points
Self cleaning, small lands and pads (0,6 mm)



H



9-point serrated
Universal Tip-style for lands, pads, leads, terminals



L



Standard 4-points crown
Self cleaning, testpads, leads solder point



H16



16-point serrated
Universal large Tip-style for lands, pads, leads, terminals



LR



Reduced 4-points crown
Self cleaning, testpads, leads solder point




Z20




Kaleidoscope
Wire Wrap and pads




R




4-point with ring
Like L, with ring for easy probe extraction



J



Connector probe
Designed for connectors



V



Tulip
For almost all applications



C




Spear
Designed for connectors


Ø 0,5
4




Q



5-point torch
Similar applications like Tip V




C32




Din Connector
Designed for connectors

Ø 0,5
3



X



4-point tapered crown
For pads, leads, lands and holes

